



## **A COMPREHENSIVE REVIEW ON HYBRID ENERGY STORAGE SYSTEM WITH BATTERY AND SUPERCAPACITOR FOR ELECTRIC VEHICLE APPLICATIONS**

**Ritika Patel**, Research Scholar, Department of Electrical & Electronics Engineering, Technocrats Institute of Technology and Science, Bhopal, India

**Devendra Sharma**, Assistant Professor, Department of Electrical & Electronics Engineering, Technocrats Institute of Technology and Science, Bhopal, India

**Saurabh Gupta** Associate Professor Department of Electrical & Electronics Engineering, Technocrats Institute of Technology and Science, Bhopal, India

### ***Abstract—***

Nowadays, the demand for electric vehicles (EVs) is rapidly increasing due to the growing concerns over environmental pollution, rising fuel costs, and the limited availability of fossil fuels. Conventional internal combustion engine vehicles face several drawbacks, including high maintenance requirements and significant emissions that contribute to environmental degradation. As a sustainable alternative, renewable energy sources such as solar and wind power are being explored to meet the global energy demand. However, to ensure a stable and reliable power supply, efficient energy storage systems are essential. Technologies like batteries and supercapacitors play a vital role in storing and managing this energy for practical use. This paper presents a comprehensive review of energy storage systems, focusing on the integration of batteries and supercapacitors for electric vehicle applications.

### ***Keywords—***

Energy Management, Converter, Electric Vehicle, Supercapacitor, Battery, Hybrid. Solar.

## **I. INTRODUCTION**

One of the primary mechanical hindrances in the field of harmless to the ecosystem vehicles is connected with the energy stockpiling framework. It is in such manner that vehicle makers are activating to further develop battery advancements and to anticipate their way of behaving precisely. A bi-directional power trade between the plug-in electric vehicle (PEV) and the air conditioner electrical network is important to play out the Vehicle to Framework (V2G) and Lattice to Vehicle (G2V) tasks. While playing out these tasks, different power converters and regulators assume a significant part as arbiters between the PEV and electric lattice. Different works have exhibited the usage of regulators for PEV's battery power management. Notwithstanding, the current regular regulators have specialized deficiencies about weakness to regulator gain, precise numerical demonstrating, unfortunate versatility, drowsy reaction to an unexpected explosion and extensive span execution handling [2].

Energy capacity is fundamental for adjusting the age and burden in power frameworks. Building a battery energy capacity framework (BESS) with resigned battery packs from electric vehicles (EVs) or plug-in hybrid electric vehicles (PHEVs) is one potential method for sponsoring the cost of EV/PHEV batteries, and simultaneously relieving estimate mistake presented by load and environmentally friendly power sources in power frameworks [3]. Lithium-particle (Li-particle) batteries are as yet the best innovation to control the Electric Vehicle (EV), because of their high power and energy thickness. Notwithstanding, the utilization of these batteries can be restricted in vehicles with a popularity for top power and extremely high energy thickness. One method for working on the presentation of the Li- particle battery and decrease its weight is to connect this battery with one more innovation of higher explicit energy as a subsequent energy source, for example Lithium-sulfur (Li-S). The improvement of Hybrid Energy Stockpiling Frameworks (HESSs) is a promising arrangement upgrading the energy management of Evs [5].

This exploration planned an energy management framework including a battery-supercapacitor

Hybrid Energy Stockpiling Framework (HESS) for electric vehicles (EV). The goal is to work on the presentation of the HESS by consolidating battery and supercapacitor highlights, representing geographical data to ensure nonstop hybridization during the drive cycle. Form Situating Framework (CPS) was utilized to decide the slant of the rode went by the vehicle [6].



Figure 1: HESS of Electric Vehicle

When At the point when the silicon carbide (SiC) power module is applied to the energy stockpiling converter of a hybrid train, under the activity of  $di/dt$  and circle stray inductance, it is not difficult to create unreasonably high voltage overshoot, which influences the battery duration and invigorates high-recurrence motions, making power gadgets endure more prominent electrical pressure. To streamline the framework format and further develop framework execution, it is incredibly important to precisely separate and assess the circle inductance [7]. With the notoriety of electric vehicles (EVs), countless EVs will turn into a weight to the future network with inconsistent charging management. It is of imperative importance to the control of the EVs charging and releasing state suitably to empower the EVs to become amicable to the network. Consequently, taking into account the potential for EVs seen as energy stockpiling gadgets, this paper proposes a multiport DC strong state transformer geography for bidirectional photovoltaic/battery-helped EV parking garage with vehicle-to-matrix administration (V2G- PVBP)[8]. Electric vehicles (EVs) are considered to alleviate energy emergency, and ecological issues because of their high productivity, and low outflows, and energy management techniques (EMSs) have been broadly contemplated to work on the exhibition of hybrid energy stockpiling frameworks (HESSs) for Evs [9].

## II. LITERATURE SURVEY

T. Mesbahi et al.,[1] presents the high level electrothermal displaying of a hybrid energy stockpiling framework incorporating lithium-particle batteries and supercapacitors. The goal is to permit the maturing parts of the parts of this framework to be considered. The improvement of a model including the electrothermal ways of behaving makes it conceivable to assess the dynamic corruption of the exhibition of the hybrid energy stockpiling framework. The portrayal of the two parts comprising the hybrid framework is completed by means of a hybrid molecule swarm-Nelder-Mead (PSO-NM) improvement calculation utilizing the trial information of a metropolitan electric vehicle. The acquired outcomes show the great presentation of the created model and affirm the plausibility of our methodology.

M. A. Islam et al.,[2] fosters a versatile neuro-fluffy deduction framework (ANFIS) control methodology based bidirectional power management plan to guarantee the ideal electrical power stream trade between the air conditioner electrical lattice and battery stockpiling framework in PEVs. This paper intends to lessen the weight on the network power side and use the unused power appropriately. The exhibition of the ANFIS model is shifted utilizing two PEVs in view of genuine power utilizations by various burdens at locally situated on five functional modes. Furthermore, a

near investigation between the ANFIS regulator and the PI regulator is completed to exhibit the viability of the proposed control by PEV battery.

S. Chai et al.,[3] proposes a point by point structure to assess end-of-life (EOL) EV/PHEV batteries in BESS application. The structure comprises of three sections. A summed up model for battery corruption is first presented. It is trailed by displaying the battery retirement process in its most memorable life. Two vehicle types — EV and PHEV — as well as two retirement modes — ostensible and practical modes — are thought of. At last, the utilization of the second-life BESS in power frameworks is displayed in a definite financial dispatch (ED) issue. This is the way second-life BESS's presentation converts into cost investment funds on power age. An improvement issue is formed to boost complete expense reserve funds in power age over the battery's subsequent life. This is finished by finding some kind of harmony between transient advantage (everyday expense investment funds) and long haul benefit (cost investment funds through help years). Mathematical outcomes approve the adequacy of the proposed system/models. They show that battery use and retirement model in its first life straightforwardly influence the presentation in quite a while second life application.

X. Zan et al.,[4] To work on the perseverance and charging adaptability of electric vehicle battery packs, this paper proposes a multi-battery block module (MBM) geography for four-stage exchanged hesitance engines (SRMs), which permits adaptable electric vehicle activity, yet in addition accomplishes quick demagnetization and excitation. By coordinating the multi-battery block module and photovoltaic (PV) board into a lopsided half-span (AHB) converter, the MBM geography is intended to supply a staggered transport voltage for the SRM drive. To work on the perseverance of battery packs, a PV board is likewise added to the geography to charge battery packs when the framework is fixed. As per the different activity prerequisites, numerous power supply modes and charging modes can be acknowledged by controlling the power gadgets in the proposed MBM geography. The recreation results in view of the MATLAB/Simulink stage and the trial results on a four-stage 8/6 exchanged hesitance engine confirm the viability of the proposed plan.

A. Avila et al.,[5] present trial results got with a high unambiguous energy and power capacity HESS model, made out of i) a Lithium-Titanate-Oxide battery to guarantee high power capacities, ii) a Li-S battery to work on unambiguous energy, and iii) a power converter in view of Gallium Nitride (GaN) gadgets to connect both battery modules, limiting simultaneously framework weight, volume and power misfortunes. The created GaN-based power converter accomplishes high productivity (96.5%) working at 300 kHz with a decreased size (0.4 L). In addition, the way of behaving of the created HESS model is tentatively assessed under standard auto profiles, for various driving situations.

T. Sadeq et al.,[6] The HESS model, electric vehicle and regulators were tried utilizing MATLAB/Simulink with three genuine drive cycles, specifically, tough, downhill and city visit, in three unique velocities 50Km/h, 60Km/h and 70 Km/h. The outcomes demonstrated the regulators figured out how to expand battery duration cycle by lessening the weight on the battery for the drive cycles. The outcomes were analyzed as far as energy utilization for the ideal versatile rule-based regulator and fluffy versatile rule-based regulator. The ideal versatile rule-based regulator ensured the HESS had the option to work ceaselessly and expand the quantity of drive cycles in a wide scope of paces and street slants.

Y. Fan et al.,[7] presents the regular high-recurrence converter structure as the item, lays out an identical model of the circuit, and quantitatively investigates the circle inductance according to a numerical perspective. For the circuit after the lined up of retention capacitor, the little sign model is utilized to investigate and uncover the job and impact of the ingestion capacitor. At last, the estimation consequences of the model are looked at through a twofold heartbeat explore. The outcomes show that the mistake between the model and the trial results is around 1%, and the impact of assessing the wanderer boundaries of the converter circuit is great, and it can offer a

hypothetical help for the choice and plan of the ingestion capacitor.

D. Qin et al.,[8] The proposed versatile bidirectional hang control is intended for opportunity EVs to make them independently accuse or release of specific power which as per every EV's condition of charge, battery limit, leaving time, and different elements to keep up with the steadiness representing things to come microgrid. In the long run, the reenactment and examination of the versatile bidirectional hang control based V2G-PVBP is given to demonstrate the accessibility of V2G-PVBP.

C. Zhai et al.,[9] proposes a prescient EMS (PEMS) for the battery/supercapacitor HESSs. In the first place, the example arrangement based speed indicator is introduced to precisely anticipate the future transient speed profile. Second, the PEMS is proposed by forming a HESS power split streamlining issue, where the HESS energy misfortune, and the battery limit misfortune are thought of. Third, a better turbulent molecule swarm enhancement calculation is introduced to take care of the planned improvement issue. Recreation results exhibit that, contrasted and the benchmark, the proposed PEMS can actually lessen the HESS energy misfortune, and expand the battery lifetime simultaneously.

M. Boycott et al.,[10] Nanogrids are supposed to assume a huge part in dealing with the steadily expanding circulated sustainable power sources. If an off-matrix nanogrid can supply completely energized batteries to a battery trading station (BSS) serving local electric vehicles (EVs), it will assist with laying out a construction for executing sustainable power to- vehicle frameworks. A scope organization issue is planned to decide the ideal measuring of photovoltaic (PV) age and battery-based energy capacity framework (BESS) in such a nanogrid. The issue is formed in view of the blended whole number straight programming (MILP) and afterward tackled by a strong improvement approach. Adaptable vulnerability sets are utilized to change the conservativeness of the hearty advancement, and Monte Carlo reenactments are done to analyze the presentation of the arrangements. Contextual investigations exhibit the benefits of the proposed applications and confirm our methodology.

X. Hou et al.,[11] inclination of clients while booking the elaborate actual hardware of various qualities. Further, a dedicatedly planned charging and releasing procedure for both the ESS and EV considering their capital expense is proposed to incorporate them into the Fixes for giving a superior adaptability and monetary benefits as well as to draw out the existence of the batteries. In view of the blended number direct programming (MILP) and the proposed model, the energy timetable of the shrewd home can be determined to ensure both the least expense and the solace for the clients. An illustrative contextual investigation is utilized to show the viability of the proposed strategy.

B. Wang et al.,[12] presents a lowlife based technique for the hybrid energy stockpiling framework (HESS) in sun oriented helped electric vehicles (EVs), utilizing another bidirectional three-level flowed (BTLC) converter. Besides, photovoltaic (PV) boards are likewise viewed as in the framework, in light of the fact that the proposed strategy is intended for sun oriented helped EV applications to accomplish a more drawn out driving reach. The proposed BTLC converter can coordinate the battery and the supercapacitor as a HESS to really moderate the power befuddle between the PV power age and the heap power utilization for the sun based helped EVs. The BTLC converter is better than the traditional equal associated bidirectional battery/supercapacitor converters according to the viewpoints of related part size decrease and control adaptability.

### III. CHALLENGES

#### 1. EV cost and battery cost

The cost is the most unsettling point for a person with regards to purchasing an electric vehicle. Notwithstanding, there are numerous motivating forces emitted by local and state legislatures. Yet, the normal condition in all strategies is that the motivators are just relevant for up to a specific number





of vehicles just and in the wake of eliminating the rebate and impetuses a similar EV which was looking rewarding to purchase unexpectedly becomes exorbitant. This tells that purchasing EV's not anymore be less expensive after a specific immersion point.

#### Battery Cost:

It's not any more stowed away from anybody that the Li-particle battery in electric vehicles is dependable till 6-7 years or barely 8 years and after the battery rot time of an electric vehicle battery its client stays with no other decision than to purchase a fresher battery which costs almost 3/4 th of the entire vehicle cost.

Battery cost will be a major problem for the EV purchasers since electric vehicles are new to both market and clients the battery issue expects something like 5 years to surface this will going to be influenced in a long run.

#### 2. Beta version of vehicles:

At this moment, both the innovation and organizations are new to the market and the items they are fabricating are perhaps confronting genuine costumers interestingly. What's more, it's almost difficult to make such a perplexing item like an auto ideal for the clients in the first go, and true to form the purchasers confronted many issues. Vehicles like RV400, EPluto 7G, Nexon all them needs to refresh their vehicle up to an extremely serious degree after client criticism and surveys.

As of late Unadulterated EV has made a great deal of changes in their strategies, programming, equipment, and not even Goodbye engines needs to update their BMS and regen programming after a ton of grievances from the clients with respect to very low reach. In this way, purchasing the vehicle from the main clump of the organization's creation would be a poorly conceived notion and could in fact give you a very terrible encounter.

#### 3. Poor Infrastructure and range anxiety:

Unfortunate foundation is among the most major problem among individuals remembering to pick electric vehicles. Poor infra doesn't just incorporate an absence of charging stations yet in addition the absence of legitimate energizing set in their home. Charging a heavier electric vehicle could be a significant issue for any electric vehicle proprietor if he/she needs legitimate arrangement (Strong MCB, wire, and earthing) close to their place.

#### 4. No Universal charger and Ecosystem (Lack of standardization):

Consistently electric vehicle-production organization has its own different charging port which is turning into an obstacle to setting up a legitimate charging biological system.

Likewise, numerous EV clients whined turning around moral difficulty for charging their vehicle in various EV-production Organization's charging stations which can affect the development of the EV business.

Absence of normalization is a revile to the Indian electric vehicle industry; it's harming the present and fate of the EV market. Consistently electric bike has its own different charging port, which influences the charging station framework in light of the fact that no particular charging station can be fabricated that can charge a wide range of electric vehicles. Likewise, the absence of normalization lessens the EV reception rate in the public eye based networks.

#### 5. Temperature Issues:

Temperature can influence the exhibition of an EV battery at a huge degree which makes EV's unseemly for excessively chilly (Uttarakhand, Meghalaya) or too hot districts like (Rajasthan, Kerala). The battery can give its ideal exhibition when it's being used under the temperature scope of 15-40 degrees.

#### 6. Very few academic and local skill awareness:

EV push is vital alongside the scholarly mindfulness and significance to the understudies of coming ages. Since the EV spare part and overhauling industry is one more fundamental piece of the development of Ev's. At the point when one is left with their broke ICE vehicle, he/she can undoubtedly find an assistance or costumer support close to them however when it's about electric

vehicles it's unquestionably a drawn-out errand to find somebody who can fix their issue.

7. Less performance for ideal economy:

IC motor driven vehicles are still far in front of electric vehicles with regards to execution. To ensure that an EV is giving the guaranteed range it turns out to be exceptionally essential to drive the vehicle at lower execution and know about greatest use of 'regen'.

8. Will increase the electricity demand at a national level:

It's simply a question of expecting the addition in electricity request when everybody in the city is utilizing exclusively electricity to charge their vehicle. It'll be a horrendous addition in the interest for electricity and at this point, we are significantly subject to consuming fossils for producing electricity.

Until we utilize sustainable wellsprings of energy for creating electricity the EV insurgency will be of no utilization.

9. Environmental concerns:

The EV upset is essential for the most populated and dirtied pieces of India like Delhi, Mumbai, and so on yet in such urban communities the significant lump of electricity is created through consuming petroleum derivatives which are identical to spreading the contamination through the ICE vehicle smoke, even the greater part of the charging stations are supposedly working upon diesel-driven electricity generator.

#### IV. CONCLUSION

Electric vehicles made their proper debut into the commercial vehicle market in the year 2019. Still there are so many challenges in the electric vehicle. The major issues occurred in the electric vehicle battery operation. Recently many of the EV is blasted due to the thermal effect. This paper presents the review of energy storage system with battery and supercapacitor for electric vehicle applications. In future, design a model for hybrid energy storage system for EV applications.

#### REFERENCES

1. T. Mesbahi, P. Bartholomeüs, N. Rizoug, R. Sadoun, F. Khenfri and P. L. Moigne, "Advanced Model of Hybrid Energy Storage System Integrating Lithium-Ion Battery and Supercapacitor for Electric Vehicle Applications," in *IEEE Transactions on Industrial Electronics*, vol. 68, no. 5, pp. 3962- 3972, May 2021, doi: 10.1109/TIE.2020.2984426.
2. M. A. Islam et al., "Modeling and Performance Evaluation of ANFIS Controller- Based Bidirectional Power Management Scheme in Plug-In Electric Vehicles Integrated With Electric Grid," in *IEEE Access*, vol. 9, pp. 166762-166780, 2021, doi: 10.1109/ACCESS.2021.3135190.
3. S. Chai et al., "An Evaluation Framework for Second-Life EV/PHEV Battery Application in Power Systems," in *IEEE Access*, vol. 9, pp. 152430-152441, 2021, doi: 10.1109/ACCESS.2021.3126872.
4. X. Zan, G. Xu, T. Zhao, R. Wang and L. Dai, "Multi-Battery Block Module Power Converter for Electric Vehicle Driven by Switched Reluctance Motors," in *IEEE Access*, vol. 9, pp. 140609-140618, 2021, doi: 10.1109/ACCESS.2021.3119782.
5. A. Avila, M. Lucu, A. Garcia-Bediaga, U. Ibarguren, I. Gandiaga and A. Rujas, "Hybrid Energy Storage System Based on Li-Ion and Li-S Battery Modules and GaN-Based DC-DC Converter," in *IEEE Access*, vol. 9, pp. 132342-132353, 2021, doi: 10.1109/ACCESS.2021.3114785.
6. T. Sadeq, C. K. Wai, E. Morris, Q. A. Tarbosh and Ö. Aydoğdu, "Optimal Control Strategy to Maximize the Performance of Hybrid Energy Storage System for Electric Vehicle Considering Topography Information," in *IEEE Access*, vol. 8, pp. 216994-217007, 2020, doi: 10.1109/ACCESS.2020.3040869.
7. Y. Fan et al., "Evaluation Model of Loop Stray Parameters for Energy Storage Converter of Hybrid Electric Locomotive," in *IEEE Access*, vol. 8, pp. 212589-212598,



2020, doi: 10.1109/ACCESS.2020.3039343.

8. D. Qin, Q. Sun, R. Wang, D. Ma and M. Liu, "Adaptive bidirectional droop control for electric vehicles parking with vehicle-to-grid service in microgrid," in CSEE Journal of Power and Energy Systems, vol. 6, no. 4, pp. 793-805, Dec. 2020, doi: 10.17775/CSEEJPES.2020.00310.
9. C. Zhai, F. Luo and Y. Liu, "A Novel Predictive Energy Management Strategy for Electric Vehicles Based on Velocity Prediction," in IEEE Transactions on Vehicular Technology, vol. 69, no. 11, pp. 12559-12569, Nov. 2020, doi:10.1109/TVT.2020.3025686.
10. M. Ban, D. Guo, J. Yu and M. Shahidehpour, "Optimal sizing of PV and battery-based energy storage in an off-grid nanogrid supplying batteries to a battery swapping station," in Journal of Modern Power Systems and Clean Energy, vol. 7, no. 2, pp. 309-320, March 2019, doi: 10.1007/s40565-018-0428-y.
11. X. Hou, J. Wang, T. Huang, T. Wang and P. Wang, "Smart Home Energy Management Optimization Method Considering Energy Storage and Electric Vehicle," in IEEE Access, vol. 7, pp. 144010-144020, 2019, doi: 10.1109/ACCESS.2019.2944878.
12. B. Wang, X. Zhang, U. Manandhar, H. B. Gooi, Y. Liu and X. Tan, "Bidirectional Three-Level Cascaded Converter With Deadbeat Control for HESS in Solar-Assisted Electric Vehicles," in IEEE Transactions on Transportation Electrification, vol. 5, no. 4, pp. 1190-1201, Dec. 2019, doi: 10.1109/TTE.2019.2939927.